

Model:TLLA23.8G24.2G-18-45
Low Noise Amplifier
23.8-24.2GHz, NF:4.5 dB, Gain:18 dB,
P1dB:13dBm
Feature :

- Ultra Wide Band: 23.8-24.2GHz
- Gain: 18dB Min
- Noise Figure: 4.5dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	23.8-24.2			GHz
增益 Gain	18			dB
增益平坦度 Gain Flatness		±0.6		dB
噪声系数 Noise Figure			4.5	dB
线性输出功率P1dB	13			dBm
输入驻波 Input VSWR			1.8	:1
输出驻波 Output VSWR			1.8	:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		120		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical :



参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	2.92mm Female	
直流偏置 Bias	Solder Pin	
尺寸 Size	32.1*29.2*11	mm
重量 Weight	/	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	
输入功率 RF INPUT POWER	
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:

Unit: mm/inchs



*****Heat Sink Required During Operation**

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-55		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLLA23.8G24.2G-18-45	Low Noise Amplifier, 23.8-24.2GHz, Noise Figure:4.5 dB, Gain:18 dB,P1dB:13dBm,12V DC,Without Heatsink	Rev.1.1
TLLA23.8G24.2G-18-45-HS	Low Noise Amplifier, 23.8-24.2GHz, Noise Figure:4.5 dB, Gain:18 dB,P1dB:13dBm,12V DC,With Heatsink	Rev.1.1