

Model:TLLA8G12G-32-15
Low Noise Amplifier
8-12GHz, NF:1.5 dB, Gain:32 dB,P1dB:15dBm
Feature:

- Ultra Wide Band: 8-12GHz
- Gain: 32 Min
- Noise Figure: 1.5dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	8-12			GHz
增益 Gain	32			dB
增益平坦度 Gain Flatness			±1.5	dB
噪声系数 Noise Figure			1.5	dB
线性输出功率Output P1dB	15			dBm
输入驻波 Input VSWR			2.0	VSWR
最大输入功率Input Max Power			20	dBm
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		100		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical :


参数Parameter	指标 Value	单位Units
输入输出接口Input /Output Connector	SMA Female	
直流偏置 Bias	Solder Pin	
尺寸 Size	32.1*29.2*11	mm
重量 Weight	300	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	
输入功率 RF INPUT POWER	20 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:

Unit: mm (inches)



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-55		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLLA8G12G-32-15	Low Noise Amplifier, 8-12GHz, Noise Figure:1.5dB, Gain:32dB,P1dB:15dBm,12V DC,Without Heatsink	Rev.1.1
TLLA8G12G-32-15-HS	Low Noise Amplifier, 8-12GHz, Noise Figure:1.5dB, Gain:32dB,P1dB:15dBm,12V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:

Gain&VSWR

