


DETAIL A(20:1)



DETAIL B(20:1)

Electrical & Environmental Characteristics

Impedance	50 Ohm
Operating Frequency	DC-50 GHz
Connector	2.4mm Female
Insertion Loss	0.05* $\sqrt{f_GHz}$
VSWR	1.25 Typ
Interface	MIL-STD-348A
Operating Temperature	-40~+165 °C

Material & Coat-Plating

Contact	BeCu C17300 GOLD PLATE
Housing	SUS303
Bead	PTFE
Item	MATERIAL & FINISH

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	2.4-KFDEL18 2.4mm FEMALE END LAUNCH CONNECTOR		
		PRODUCT SPEC			
MATERIAL SEE TABLE	FINISH SEE TABLE	APPLICATION SPEC			
		WEIGHT			
CUSTOMER DRAWING			SCALE 4	SCALE 4: 1	SHEET1 OF 1
					RVE 1