

Model:TLPA30G36G-46-46
Power Amplifier
30GHz-36GHz, Gain:46dB, Psat:46dBm
Feature:

- Ultra Wide Band: 30GHz-36GHz
- Gain: 46dB Min
- Psat Output Power: 46 dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	30-36			GHz
增益 Gain	46	50		dB
增益平坦度 Gain Flatness		±3	±5	dB
线性输出功率P1dB		44		dBm
饱和输出功率Psat	46	47		dBm
输入驻波 Input VSWR		1.5	2.0	:1
输出驻波 Onput VSWR				:1
直流电压 DC Voltage		28	30	V DC
直流电流 DC Supply Current		20	32	A
阻抗 Impedance	50			Ohms


机械特性 Mechanical :

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	2.92mm WR28	
直流偏置 Bias	D-SUB-9	
尺寸 Size	220X200X35	mm
重量 Weight	6000	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	30
输入功率 RF INPUT POWER	+5dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:



*****Heat Sink Required During Operation**



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-40		+60	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	30,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLPA30G36G-46-46	Power amplifier 30GHz-36GHz, Gain:46dB, Psat:46dBm, 28V DC, Without Heatsink	Rev.1.0
TLPA30G36G-46-46-HS	Power amplifier 30GHz-36GHz, Gain:46dB, Psat:46dBm, 28V DC, With Heatsink	Rev.1.0