


### Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	500V
VSWR	1.25Max
Insertion Loss	≤0.50dB
Operating Temperature	- 55~+125℃


### Material & Coat-Plating

Inner Conductor	BE-CU, Gold Plated
Dielectric	PTFE&PEI
Body	BE-CU, Gold Plated&Stainless Steel, Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model  2.92-SMP-KKG 2.92mm Female to SMP Female adaptor			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	
		CUSTOMER DRAWING			SHEET 1 OF 1	RVE 1



1 通道1 起始:10.0000MHz -- 终止:40.0000GHz



2 通道1 起始:10.0000MHz -- 终止:40.0000GHz

	扫描类型	起始频率 (GHz)	终止频率 (GHz)	扫描点数	中频带宽 (Hz)	扫描时间 (s)	端口1, 2功率 (dBm)
通道1	线性扫描	0.010000000	40.000000000	801	1000	0.779105	-5.00, -5.00