

**Model: TMPA-050075-3818-15**
**Power Amplifier**
**50-75 GHz, Psat:18 dBm, Gain:38 dBm**
**Feature:**

- Frequency Range: 50-75 GHz
- Gain:38 dBm Type
- Output Power Psat: 18 dBm Type
- Good Power and Gain Flatness

**电气特性 Electrical:**

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	50-75			GHz
增益 Gain	35	38		dB
饱和输出功率Psat		18		dBm
输入驻波 Input VSWR		2.5		:1
输出驻波 Output VSWR		2.5		:1
直流电压 DC Voltage		5		V DC
直流电流 DC Supply Current		550		mA

**机械特性 Mechanical :**

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	WR-15/UG-385/U	
直流偏置 Bias	Solder Pin	
尺寸 Size	60*45*24	mm
重量 Weight	/	g


**绝对最大值 Absolute Maximum Ratings:**

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF INPUT POWER	TBD
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


 Available 220V System  
 Benchtop Amplifier

外形尺寸 Outline Drawing:

Unit: mm(Inches)



OBSERVE PRECAUTIONS  
ELECTROSTATIC SENSITIVE  
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	0		+65	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMPA-050075-3818-15	Power Amplifier 50-75 GHz, Psat:18 dBm Type, Gain:38 dBm Type,WR-15	Rev.1.1